

PEVC3107E (60kW - 240kW)

Ultra Fast DC Charger

PEVC3107E is up to 240kW output with CE certifications.



CCS2

CCS1

CHAdMO



- Multi-standard: CCS1, CCS2, CHAdMO
- Network or standalone operation
- Optional RFID/App etc. for user identification and management
- Efficiency > 95%, Power Factor ≥ 0.99
- Multiple protection to ensure users' safety
- 7 inch color touch screen with user friendly interface
- OCPP 1.6 JSON (Comply with latest OCPP protocol as SINO is the member of OCA)
- IK10& IP54, for indoor and outdoor applications
- Customization available
- Accepts two plugs simultaneous charging

Applications

- EV bus station
- Highway gas/service station
- Parking garage
- Commercial fleet operators
- EV infrastructure operators and service providers
- EV dealer workshops



Power Specifications

Input Connection	3-Phase : 3P+N+PE
Input Voltage	400Vac $\pm$ 10%
Frequency	50Hz or 60Hz
THDi	$\leq$ 5%
Power Factor	$\geq$ 0.99
Output Voltage	150Vdc - 1000Vdc
Max. Output Current	250A
Rated Power	60kW - 240kW

User Interface & Control

LCD Display	7" Color Touch Screen(12" Customization)
User Authentication	RFID(ISO/IEC 14443)(APP/ Credit Card Customization)
LED Indicator	Green/Blue/Red
Charger Connector	CCS2 (CCS1 / CHAdeMO Optional)
Number of Charging Interface	1 or 2
Energy Measuring	DC meter, with 1% accuracy

Communication

Backend	Ethernet (4G Optional)
Charging Protocol	ISO 15118 , DIN 70121
Backend Protocol	OCPP 1.6 J (OCPP2.x Coming soon)

Protection

Residual Current Device	Yes
Internal Fuse	Yes
Electrical Protection	Over/Under Voltage Protection, Over Current Protection, Short Circuit Protection, Over Temperature Protection, Lightning Protection, Ground Fault, Surge Protection

Environmental

Operating Temperature	-30 $^{\circ}$ C - +50 $^{\circ}$ C
Storage Temperature	-40 $^{\circ}$ C - +75 $^{\circ}$ C
Operating Humidity	5%-95% RH, Non-Condensing
Operating Altitude	$\leq$ 2000m
IP, IK Level	IP54, IK10
Cooling Method	Fan Cooling

Mechanical

Product Dimension	700mm*550mm*1800mm(W*D*H) or 750mm*750mm*1900mm(W*D*H)
Package Dimension	950mm*720mm*1950mm(W*D*H) or 1000mm*920mm*2050mm(W*D*H)
Charging Cable Length	5m (Customizable)
Weight	363kg(Net) / 380kg(Gross) or 411kg(Net) / 428kg(Gross)
Mounting	Free Standing

Certifications

Certificate	IEC62196-1, IEC62196-3, IEC 61851-1, IEC61851-23, IEC61851-24
Safety	CE

